

SPECIFICATIONS

No. ISA3587B

Date. Oct.25, 2023

Approved by M.Fujimoto

Checked by Y.Hanaoka

Written by R.Guo

TWS(ϕ 25) SERIES

PUSHBUTTON SWITCH

TYPE A Δ S3 $\square\square$ N \times

Operation type \square Button color \times
 Contact arrangement $\square\square$

1. Applicable standard

JIS C 8201-5-1
 IEC60947-5-1
 EN 60947-5-1 (TUV Approval)
 GB/T14048.5(CCC Certification)
 UL508 (UL Listing)
 CSA C22.2 No.14 (CSA Certified)

2. Operating conditions

- (1) Ambient temperature -25 to +50°C (no freezing)
- (2) Relative humidity 45 to 85% (no condensation)
- (3) Storage temperature -40 to +80°C (no freezing)

3. Ratings

- (1) Rated insulation voltage 600V
- (2) Thermal current 10A
- (3) Rated operating voltage and rated operating current

		Rated operating voltage					
		24V	48V	50V	110V	220V	440V
Rated operating current	A	Resistive load (AC-12)	10A	—	10A	10A	2A
	C	Inductive load (AC-15)	10A	—	7A	5A	1A
	D	Resistive load (DC-12)	10A	5A	—	2.2A	—
	C	Inductive load (DC-13)	5A	2A	—	1.1A	—

Note) The operating current is classified according to the JIS C 8201-5-1 making and breaking current capacities.

- (4) Minimum applicable load (reference value) 3V AC/DC, 5mA

4. Constructions

- (1) Outside view See attached sheet
- (2) Degree of protection
 - (a) Operation units (panel front side) IP65
 - (b) Contact block IP20
- (3) Operation type — (Δ) Momentary (B), Alternate (O)
- (4) Button style Flush
- (5) Contact arrangement — ($\square\square$) 1a(10), 1b(01), 1a-1b(11), 2a(20), 2b(02), 2a-2b (22), 4a (40), 4b (04), 1a-3b (13), 3a-1b (31), 3a (30), 3b (03), 1a-2b (12), 2a-1b (21)
- (6) Button color —(\times) Black(B),Green(G),Red(R),Yellow(Y),Blue(S), White(W)
- (7) Terminal style M3.5 terminal screw +/- screw head

(8) Applicable wire / Recommended tightening torque

Applicable wire		Maximum number of installed	Recommended tightening torque (N·m)
Solid wire	ϕ 0.5~1.6mm (AWG14~22)	2	1.0~1.3
	ϕ 1.7~2.0mm (AWG12)	1	1.2~1.3
Strand wire	0.3~2.0mm ² (AWG14~22)	2	1.0~1.3
	2.1~3.5 mm ² (AWG12)	1	1.2~1.3

(9) Panel thickness 0.8 to 6mm

(10) Panel cut-out ϕ 25.5^{+0.5}mm

5. Characteristics

(1) Insulation resistance 100M Ω minimum (measured with a 500V DC megger)

(2) Dielectric strength 2,500V AC, 1minute

(3) Contact resistance 50m Ω maximum (initial value)

(4) Vibration resistance

(a) Operating extremes Frequency 5 to 55Hz, Amplitude 0.5mm

(b) Damage limits Frequency 30Hz, Amplitude 1.5mm

(5) Shock resistance

(a) Operating extremes 100 m/s²(b) Damage limits 1,000 m/s²

6. Life

(1) Mechanical life (without load)

(a) Momentary 5,000,000 operation minimum

(b) Alternate 500,000 operation minimum

(2) Electrical life (rated load)

(a) Momentary 500,000 operation minimum

operating frequency : 1,800 operations/hour maximum, Duty Rate : 40%

(b) Alternate 500,000 operation minimum

operating frequency : 900 operations/hour maximum, Duty Rate : 40%