

Doc No.	D1B010
	D2B009
	D5B127

EU Declaration of Conformity

Identification of the Product	Electronic Timer
Name and address of Manufacturer IDEC CORPORATION 2-6-64 Nishimiyahara, Yodogawa-Ku, Osaka 532-0004 Japan	Name and address of the authorized representative : IDEC ELEKTROTECHNIK GmbH Heselstuecken 8, 22453 Hamburg, Germany

This declaration of conformity is issued under the sole responsibility of the manufacturer.

Object of the declaration :

Series Name – GT5Y and GT5P Series
Model No. – Details are as per attached sheet

The object of the declaration described above is in conformity with the relevant EU harmonization legislation :

2014/30/EU	Electromagnetic Compatibility Directive
2014/35/EU	Low Voltage Directive
2011/65/EU	Restriction of the use of certain hazardous substances (RoHS) Directive

Applied Union harmonized legislation and references to the relevant harmonization standards used or references the other technical specifications in relation to which conformity is declared.

EN 61812-1:2011
EN 50581:2012

Where applicable, the notified body

Additional Information :

Signed for and on behalf of the above named manufacturer :


Place and date of issue : Japan, 20 April, 2016
Japan, 21 July, 2017 (Revised)
Name, function : Atsushi Matsumoto, Executive Officer,
Quality Assurance Center
Signature :

Atsushi Matsumoto



Doc No.	D1B010
	D2B009
	D5B127

20 April, 2016
 21 July, 2017 (Revised)
 Page 1 of 1



GT5Y Series

GT5Y - 4 S N 1 A100 -*****
 (1) (2) (3) (4) (5) (6) (7)

- (1) Series GT5Y
- (2) Contact Configuration 2: DPDT, 8 Terminals
4: DPDT, 14 Terminals
- (3) Terminal Configuration S: Soldering and Plug-In Type
P: Printed Wiring Board Type
- (4) Function Mode N: On Delay Mode
V: Interval On Mode
F: Flicker Mode
- (5) Time Range 1: Selectable Time Range 1s/10s/1min/10min
3: Selectable Time Range 3s/30s/3min/30min
6: Selectable Time Range 6s/60s/6min/60min
- (6) Operating Voltage A100: 100 to 120V AC
A200: 200 to 240V AC
D12: 12V DC
D24: 24V DC
- (7) Manufacturer Control Number (may be followed)
*****: Additional letters and/or numbers (may be including hyphens)

GT5P Series

GT5P - N 1S A100 -*****
 (1) (2) (3) (4) (5)

- (1) Series GT5P
- (2) Function Model N: On Delay model
F: Flicker model
P: One shot model
- (3) Time Range 1S: 01s-1s
3S: 01s-3s
6S: 0.1s-6s
10S: 0.2s-10s
30S: 0.5s-30s
60S: 1s-60s
3M: 3s-3min
6M: 6s-6min
10M: 10s-10min
- (4) Operating Voltage A100: 100 to 120V AC
A200: 200 to 240V AC
AD24: 24V AC / 24V DC
D12: 12V DC
- (5) Manufacturer Control Number (may be followed)
*****: Additional letters and/or numbers (may be including hyphens)