



Product Service

CERTIFICATE

No. Z10 013332 0517 Rev. 00

Parameters:

Power supply: 24VDC ±10% (converter power supply)
 24VDC +20%/-30% (battery)

Power consumption: max. 6W (without load)

Protection range: max. 5.0m

Response time: min. 60ms

Operating temperature: -10°C ... +50°C

Protection class: IP65

Tested according to:

2006/42/EC
 EN 61496-1:2013
 IEC 61496-3:2008
 IEC 61508-1:2010 (SIL2)
 IEC 61508-2:2010 (SIL2)
 IEC 61508-3:2010 (SIL2)
 IEC 61508-4:2010 (SIL2)
 IEC 62061:2005
 IEC 62061:2005/AMD1:2012
 IEC 62061:2005/AMD2:2015 (SILCL 2)
 EN ISO 13849-1:2015 (Cat 3, PI d)

Factory(ies):

075940

Model(s):

SE2L-H05LPX

SE2L - H05LPX
I

- I. End of cable
- Blank: Flying lead wire
- C: with IP65 connector



TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證書 ◆ CERTIFICADO ◆ CERTIFIKAT ◆ CERTIFICADO ◆ CERTIFICAT